

SLIDING MODULE FOR ELECTRONIC DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application is related to U.S. Patent Application (Attorney Docket No. US37430, application Ser. No. 13/164,301, filed on Jun. 20, 2011), entitled "SLIDING MODULE FOR ELECTRONIC DEVICE", by Duan et al. This application has been filed and has the same assignee as the present application. The above-identified applications are incorporated herein by reference.

BACKGROUND

[0002] 1. Technical Field

[0003] The present disclosure generally relates to electronic devices, and particularly to a sliding module for an electronic device.

[0004] 2. Description of Related Art

[0005] Portable electronic devices such as mobile phones, laptops, and personal digital assistants (PDAs) are widely used. As such, the sales and use of slide-type portable electronic devices have been on the increase. A slide-type portable electronic device has two housings, which can open and close relative to each other with the use of a slide mechanism.

[0006] However, the slide-type devices typically only allow the two housings to slide parallel to each other. Therefore, when the slide-type is placed horizontally, it can be difficult for users to view a display screen on the housing.

[0007] Therefore, there is room for improvement within the art.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Many aspects of the tilt mechanism for electronic device can be better understood with reference to the following drawings. The components in the drawings are not necessarily to scale, the emphasis instead being placed upon clearly illustrating the sliding module for electronic device. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the several views.

[0009] FIG. 1 is an exploded, isometric view of an electronic device according to an exemplary embodiment.

[0010] FIG. 2 is similar to FIG. 1, but shown from another angle.

[0011] FIG. 3 is an exploded, isometric view of a hinge assembly used in the electronic device shown in FIG. 1.

[0012] FIG. 4 is an isometric view of the electronic device of FIG. 1 in a closed orientation.

[0013] FIG. 5 is an isometric view of the electronic device of FIG. 4 in an open orientation.

[0014] FIG. 6 is similar to FIG. 5, but shown from another angle.

DETAILED DESCRIPTION

[0015] FIG. 1 and FIG. 2 show an exemplary embodiment of a sliding module 100 applied in an electronic device, such as a mobile phone, or a personal digital assistant. The sliding module 100 can be in a closed orientation and a tilted open orientation. The sliding module 100 includes a first section 10, a second section 20, a pivot plate 30, a pair of hinge modules 40, and a sliding member 50. In the closed orientation, the first section 10 and the second section 20 overlap each other. In the tilted open orientation, the first section 10 is tilted relative to the second section 20 for better viewing.

[0016] The first section 10 defines two retaining grooves 12 at opposite sides thereof. A bottom portion of each retaining groove 12 is protruded outward to form a cavity 13 and a protruding wall 14 surrounding the cavity 13. A post 15 is fixed in the cavity 13, and two ends thereof extend out from the protruding wall 14. A connecting member 16 is disposed at a corner of the first section 10. The connecting member 16 includes a top wall 162, a first sidewall 164 and a second sidewall 166. The first sidewall 164 and the second sidewall 166 are connected at opposite sides of the top wall 162, thereby surrounding a receiving space for receiving the sliding member 50. The second sidewall 166 defines a pivot hole 1662 for rotatably connecting to the sliding member 50. In this exemplary embodiment, the connecting member 16 is welded to the first section 10. Understandably, the connecting member 16 may be integrally formed with the first section 10.

[0017] The second section 20 defines two notches 22 at one side thereof, and defines a wedge groove 24 at one end of a surface thereof for slidably receiving the sliding member 50. A hinge barrel 26 is formed on an opposite surface of the second section 20 adjacent to each notch 22. A receiving hole 262 is defined at one end of each hinge barrel 26 for receiving a corresponding hinge module 40.

[0018] The pivot plate 30 includes a main body 32 and two support arms 34 formed at two sides of the main body 32. Each support arm 34 includes a connecting arm 36, a first hinged portion 362 and a second hinged portion 364 connected to two ends of the connecting arm 36. The first hinged portion 362 defines a first through hole 3622 for receiving the post 15 in the first section 10. The second hinged portion 364 defines a second through hole 3642 for fixing one portion of the hinge module 40.

[0019] Referring to FIG. 3, the hinge module 40 includes a washer 41, a sleeve 42, a resilient member 43, a follower 44, a cam 45, and a shaft 46. The cam 45, the follower 44, and the resilient member 43 are fitted over the shaft 46, and are received in the sleeve 42. The washer 41 is latched to one end of the shaft 46 with the above elements to assemble a unit. The follower 44 is non-rotatably engaged in the sleeve 42. The sleeve 42 can be inserted into the hinge barrel 26 from the receiving hole 262 and cannot rotate relative to the hinge barrel 26. The cam 45 can be inserted into the second through hole 3642 of the second hinge portion 364, and is non-rotatably engaged with the second hinge portion 364 of the pivot plate 30. The follower 44 includes peaks and valleys, and the cam 45 can slide over the peaks of the follower 44 to allow the cam 45 to rotate relative to the follower 45.

[0020] The sliding member 50 includes a sliding block 52 and an extending end 54 integrally formed together. The sliding block 52 is substantially wedged-shaped, and is slidably received in the wedge groove 24 of the second section 20. The extending end 54 can be received in the connecting member 16. A pin 56 is formed on the extending end 54 for being received in the pivot hole 1662 of the connecting member 16 to allow the sliding member 50 to be rotatably connected to the first section 10.

[0021] In assembly, referring to FIG. 4, each assembled hinge module 40 is received in a corresponding hinge barrel 26 of the first section 10 from the receiving hole 262. The sleeve 42 is non-rotatably engaged with the hinge barrel 26. The first hinged portion 362 of the pivot plate 30 is rotatably connected to the post 15 of the first section 10. The second through hole 3642 of the second hinged portion 364 receives the cam 45 of the hinge module 40 to non-rotatably connect the pivot plate 30 to the hinge module 40. Then, the sliding block 52 of the sliding member 50 is received in the wedge groove 24 of the second section 20. The extending end 54 of